



# 容積式平面 自動包裝機

Rectangular Bag Packing Machine  
(Volumetric weighing type)

超音波黏合切割  
Ultrasonic sealing and cutting

滑動容積式充填系統  
Volumetric weighing system

方便更換原物料  
Quickly changing ingredients

適用於不織布、PET/尼龍網布、  
環保玉米澱粉等系列包裝材質及  
多樣化填充內容物。

You can use different filters such as  
PET/Nylon, bio-degradable,  
non-woven...etc.

## 滑動容積式充填系統

### Volumetric weighing system

容積範圍內可任意調整、適合粉粒狀原物料  
It's easy to adjust the volume and it's suitable for  
granule such as ground coffee and tea fanning.

## 多次投料功能

### Multiple filling function

可擴增計量克數範圍，可用於大包裝產品  
It can increase the filling range, suitable for  
big packages.

## 提供完整設定功能

### Comprehensive setting function

觸控人機面板，提供完整的設定功能，可依照需求  
調整多項參數，提供使用者最大操作彈性  
You can easily operate this machine with touch  
panel screen. You can adjust the parameters  
according to your demand.

## 符合安全衛生標準

### Comply with safety and health standard

內容物接觸組件採用不鏽鋼材質，  
符合安全衛生標準

All the routes contacted with ingredient are made  
by stainless steel.

# AI180+VSD50

包裝速度 Capacity	Max. 60 bag/min 取決包裝原物料與重量不同而有差異 It depends on different ingredient and weight.	氣壓需求 Air Supply	6kg /cm <sup>2</sup> (0.6 MPa)
包裝材質 Packing Material	不織布, 尼龍網布/PET網布, PLA等材料. Non woven , Nylon/PET mesh, PLA...etc.	外型尺寸 Dimension	1100mm(L)x750mm(W) x2165mm(H)
包裝方式 Packing Method	超音波黏合切割 Sealing and cutting by ultrasound	重 量 Weight	320 Kg
成品尺寸 Bag Size	70mm*90mm or 74mm*90mm (其他尺寸:可另選購製袋成型器) For other sizes, you need to purchase additional bag formers.	標準配備 Standard Accessories	內袋製袋成型器 觸控人機面板 靜電消除器裝置 超音波控制箱 滑動容積計量裝置 料槽攪拌器機構組 下料振動機構 料槽無料警報 包材廢料收集裝置 Inner bag chute Touch panel HMI Static Ionizing Generators Ultrasonic control box Slide doser weighing system Hopper agitator Fluidizer to prevent bridging Empty hopper alarm Waste collection device
計量範圍 Filling Range	13cc-63cc (包裝原物料不同,而有所差異) Weighing range will be different according to different ingredient.		
計量方式 Weighing System	滑動容積式充填系統：可在範圍內調整容積大小，可依照需求調整充填重量。 充填物料項目規範平均粒徑大於0.5mm和小於5mm，含水率低於5%以下。 It's easy to adjust the volume according to your demand. Recommend ingredient type: Average particle size more than 0.5mm and less than 5mm. Moisture content less than 5%	選購配備 Option	輸送帶單元 Conveyer
電 源 Power Supply	AC220V,50/60Hz,3P, 3KW (可配合客戶電壓需求做調整) Can be transformed to local voltage		

## 規格尺寸 Standard sizes

